

32-CH AHD DVR

1080P



Main Features

- Support multiple high-definition network camera access
- Support VGA, HDMI 1080P full HD output simultaneously
- Support GB28181 & Onvif
- Supporting web, CMS, center platform management software MYEYE, provide SDK development
- Supports multiple cloud technology, network penetration, alarm information pushed to your phone and other functions
- Support multiple network services (support DHCP, FTP, DNS, DDNS, NTP, UPNP, EMAIL, 3G, WIFI, IP searches, Alarm Center, etc.)

Technical Features



	Model	AIS-3210NVR
System	Main processor	Hi 3535
	Operating System	Embedded
	System Resources	Simultaneous multi-channel real-time recording, playback,
Operator interface	Operator interface	16-bit true color graphic menu operation interface, support
	Preview	1/4/8/16/24/3
Video Audio	Video standards	PAL(625TVL,50f/s); NTSC(525TVL,60f/s)
	Video compression	H.264(Main Profile)
	Display quality	VGA,HDMI: HD
	Playback quality	5M/3M/1080P/960/720P
	Recording	32*960P
	Motion detection	Support
Record	Audio compression	G.711a
	intercom	Support
	Recording mode	Manual>Alarm>Video Detection>Continuous
Storage &	Local Playback	2*5M/4*3M/4*1080P/8*960P real-time
	Search mode	search by Time/calendar/event/channel
	Space Occupation	video: CIF 4~5G/ day*channel, D1 8~10G/ day*channel, 1080P ~40G/ day*channel; audio: 691.2M/ day*channel
Interface	Record Storage	HDD or network
	Backup mode	Network backup, USB hard disk, USB burner, SATA burner
	Video input (IP)	8*5M/16*3M/24*1080P/32*960P
	Video output	1ch VGA, 1ch HDMI HD
	Video input (BNC)	N/A
	Audio I/O	1/1
	Alarm I/O	0/0
	Network interface	1*RJ45
	PTZ control	1*RS485, Supports 18 kinds of PTZ protocol
	USB interface	2*USB 2.0
Other	Hard disk	3*SATA (Single maximum support 4T)
	ONVIF	Support
	Power supply	12V/4A or 12V/5A
	Power Consumption	<10W (Without HDD)
	Temperature	0?~+55?
	Humidity	10%~90%
	Atm	86kpa-106kpa
	dimension	mm(H)* mm(W)
	weight	2.40 KGS