

4-CH AHD DVR

1080P



Main Features

- Support multiple high-definition network camera access
- Support VGA, HDMI 1080P full HD output simultaneously
- Support GB28181 & Onvif
- Supporting web, CMS, center platform management software MYEYE, provide SDK development
- Supports multiple cloud technology, network penetration, alarm information pushed to your phone and other functions
- Support multiple network services (support DHCP, FTP, DNS, DDNS, NTP, UPNP, EMAIL, 3G, WIFI, IP searches, Alarm Center, etc.)

Technical Features



Model		AIS-4108NVR
System	Video Compression Format	H.264
	Main Processor	HI3520D
	Video System	NTSC / PAL
	Operation System	Embedded Linux
Video	Video Input	4CH 1080P
	Video Output	1 x VGA / 1 x BNC / 1 x HDMI (1920*1080)
Audio	Audio Input	NO
	Audio Output	1CH RCA
Recording	Recording Channel	4CH 1080P Real Time
	Resolution	NTSC – 1080P (1920 x 1080) / 960P (1280 x 960) / 720P (1280 x 720)
		PAL - 1080P (1920 x 1080) / 960P (1280 x 960) / 720P (1280 x 720)
Playback	Recording Mode	Manual / Alarm / Video Detection / Continuous
	Playback Channel	1CH 1080P Real Time
	Search Mode	Time / Date / Alarm / Motion Detection / Exact Search
	Playback Mode	Normal Play / Fast Forward / Fast Rewind / Frame by Frame
	Playback Software	General H.264 Player V1.7.0.
Storage	HDD Interface	2 x SATA Fixed HDD
	Capability	SATA HDD up to 4TB each
Backup	USB Disk	3 x USB 2.0 port
	Backup Format	H.264 (only for Playback Software - General H.264 Player V1.7.0.)
	Backup Mode	Network download / Flash USB / movable HDD/SATA HDD / DVD-RW
Network	Interface	RJ45 port / 10M / 100M / 1,000Mbps Ethernet
	Protocol	TCP/IP, DHCP, DDNS, DNS, PPPoE, UPNP, NTP, SMTP
	CMS Program	General_CMS_Eng_V3.0.7.7.T (up to 128 Video channels Platform)
	Mobile phone Support	iPhone / iPad, Android, BlackBerry, Symbian, Windows Mobile Pro
	Computer System Support	Windows 2000, XP, Vista, 7, 8 / Mac OS x 10.6/10.7
	Compatible Browser	Google Chrome, Internet Explorer, Mozilla Firefox, Safari
	3G/WIFI	USB Dongle 3G/WIFI (Plug-and-Play)
	Free DDNS	iCloud Free DDNS Server (P2P)
	IP Camera Protocol	ONVIF 2.0 / 2.2 Version Platform Protocol
	Simultaneous Remote Viewers	6 Users Online
Others	Operating Temperature	0°C ~ 55°C