

WALL SPEAKERS 10/20 WATT



SPECIFICATION:

Model	AIS - W20	AIS - W40	AIS - W60
Power Taps @100V	20W	40W	60W
Power Taps @ 70V	10W	20W	30W
Impedance	90dB±3dB	91dB±3dB	92dB±3dB
ISPL(1W/1M)	Black-COM- Green-500Ω White-1KΩ	Black-COM Green-250Ω White-500Ω	Black-COM Green-167Ω White-330Ω
Max. SPL (Rated W/1M)	90-20KHz	90-20KHz	90-20KHz
Frequency Response (-10dB)	IPx6	IPx6	IPx6
Finish	105 x 75 x 280mm	105 x 75 x 480mm	105 x 75 x 680mm
Speaker Driver	2 x 3.5"	4 x 3.5"	6 x 3.5"
IP Rate	2.2Kg	3.9Kg	5.6Kg

Features

- Built-in 100v/70v transformer
- Weatherproof column type loudspeaker
- IP66 waterproof level
- 6 × 3.5" full range driver
- IPower taps at 60W @100V
- Aluminum enclosure & grille in white
- A pair of metal mounting brackets are supplied

Description

The W Series is a weatherproof outdoor column speaker built-in 70v/100v transformer. The 70v/100v transformer technique reduces line losses on longer distance and allows easy parallel connection of multiple loudspeakers.

The built-in 6 units 3.5" full range speaker drivers are designed of wide frequency response 90-20KHz, the multiple power taps of 20 - 60W could meet different applications varies from room size and ambient noise surroundings.

The aluminum enclosure and grille are of white color. It is also designed of weatherproof and heavy damage proof finish. Easy and secure wall mount installation in outdoor area through the supplied pair of metal mounting brackets.

* Models may vary from time to time due to continuous improvement in product design, features, technology and stability for a better user experience.