# SMOKE DETECTOT (DC)

MODEL NO: RFS- SD501

### DESCRIPTION:

**SD501 Smoke Detector** provide battery powered smoke detection and alarm functions with in a single unit.

Advanced electronics in conjunction with a photoelectric Smoke sensing chamber provide early detection of fire and high immunity against unwanted alarms.

**SD501 smoke detector** are powered by a **10-year lithiumion** battery and do not require a mains supply. An automatic switch disconnects power from the unit when it is removed from its base.

## **TECHNICAL FEATURES:**

- Photoelectric Smoke Sensor
- Switch function disconnects power when removed from base
- Test button verifies battery and alarm operation
- Hush feature to temporarily silence unwanted alarms
- Loud 85 dB sounder to alert occupants
- 30 day low battery warning signal
- Integrated indicator provides visual indication of an alarm condition

# SMOKE DETECTOT (DC)

MODEL NO: RFS- SD502

#### DESCRIPTION:

**SD502 Smoke detector** provide battery powered smoke detection and alarm functions with in a single unit.

Advanced electronics in conjunction with a photoelectric smoke sensing chamber provide early detection of fire and high immunity *against unwanted alarms.* 

*SD502 Smoke detector* are battery powered, do not require a main supply and are suitable for general residential applications.





Models may vary from time to time due to continuous improvement in product design, features, technology and stability for a better user experience.



