


FIRE DETECTION SYSTEM



EXIT LIGHTING SERIES

MODEL NO: CFS-EXT300L, CFS-EXT300R, CFS-EXT300LR, CFS-EXT300D

Alco provides a complete range of exit and emergency lighting as an integral part of Fire Detection System, which has a number of varieties in terms of signage.

Our Exit and Emergency lights consist of a conventional indication sign and specially designed to be used in different situations in order to indicate with accuracy.

TECHNICAL FEATURES:

- Lighting Source: Led

- Lighting Wattage: 6w

- Backup Time: Upto 90 Minutes - Power Source: Ni-cd (6v, 2.8ah)

- Unit Size: 270 x 310 x 75(mm)
























































TECHNICAL FEATURES:

MODEL NO: CFS-EXT301


- Voltage: 220-240V 50 / 60HZ.
- AC Power: 3.5w MAX
- Battery: Ni-Cad 4.8v / 650mAH
- Emergency Duration: **90 Minutes**
- Lighting Source: 14PCS, SMD 2835 LED, CCT 6000K for LED escape sign.
- Test Facility: Auto Test (Self Test and Self Diagnostic) or CAN Bus Control.



TECHNICAL FEATURES:

MODEL NO: CFS-EXT302

- Voltage: 220 240V 50 / 60HZ.
- AC Power: 3.5w MAX.
- Battery: Ni Cad 4.8 V / 650 mAH.
- Emergency Duration: 3 hour.
- Lighting Source: 14PCS, SMD 2835 LED, CCT 6000K for LED escape sign.
- Test Facility: Auto test (self test and self diagnostic) or CAN BUS control.



TECHNICAL FEATURES:

MODEL NO: CFS-EXT303

- LED 120 / 347V AC input.
- Injection moulded thermoplastic ABS housing.
- Innovative, snap-together design.
- Wall, side or celling mounting.
- Battery backup for 3 hours emergency duration.
- 24 hours Charging Time.
- Battery overcharge protection.
- Charging LED indicator and push to test button.
- Working Temperature: -10 50°C.
- Working Humidity: <90%.
- Used in Commercial / Residential areas.



* Different Arrow Option Available



























EMERGENCY LIGHTING SERIES

* Technical features may vary according to lighting design series.

DESCRIPTION:

The Emergency Light is capable to switch between the lamps and has the ability to switch either one LED lamp or both based on personal preference. This Emergency Light is suitable for wall mounting.

TECHNICAL FEATURES:

MODEL NO: CFS-EMG 300

- Backup Time: Upto 3 hours (Fully Charged)

- Power Source: Ni-cd (6v, 2.8ah)

Unit Size: 270 x 310 x 75Lighting Source: LedLighting Wattage: 3w



TECHNICAL FEATURES:

MODEL NO: CFS-EMG 301

- Certificate: UL and CUL.
- The housing is adopt with high precision molding.
- Color of housing is white, material is fire retardant ABS.
- Innovative, universal mounting
- Long life LED light source.
- Double face configuration (also can be used as single side).
- Replaceable directional arrow inserts are easily removed and reinserted.



TECHNICAL FEATURES:

MODEL NO: CFS-EMG 302

- Voltage: 220-240V 50 / 60HZ
- AC Power: 9W MAX.
- Battery: Ni-CAD 3.6v / 1800AH or Ni-CAD 3.6V / 2500mAH.
- Emergency Duration: 1.5 hour or 3 hour.
- Lighting Source: 20PCS, SMD 2835 LED, CCT 6000K.
- Type: Maintained or AC & EM.


































San Carlos Business and Technology Park, Industrial Road, CA 94070 - USA

Email: enquiry@alcosolutions.net

Web: www.alcosolutions.net

