



# **SECURITY SOLUTIONS**



# ABOUT


Alco is one of the leading intelligent solution providers of Fire Detection System and Security System in the United States of America. Based in California since 1992, we have grown to deliver the most innovative building management solutions (BMS) for commercial and industrial establishments around the globe.

Alco is committed to deliver effective solutions that can help our customers. Our supplied products are designed to cater our customers in the most effective manner and we take that responsibility very seriously.

Our smart and effective Building Solutions has given us an opportunity to diversify and explore new business opportunity in the market and we are extremely delighted to penetrate successfully in various large and medium scale projects.



Alco Security Solution is widely used to monitor public area to ensure safe and secure environment.




Also understands the importance of safety and our CCTV solution provides a secure monitoring environment for all types of commenal and public area.



Also CCTV Solution are widely used in various commercial and private sectors such as corporate offices, restaurant, hospitals, school etc. To provide quality surveillance our solution are also widely used in the residential sector to ensure safety.

We understand that busy public area such as parking spaces have many occupancies through out the day. Alco offers a wide range of cctv solution to manage such situations making it very easy for all our client.





# AI LITE SERIES

STATE OF THE ART HIGH DEFINITION



H.265+



ONVIF



VCA



PoE



Defog



256GB



SIP



Plugin-free



Cyber Security

**H.265+ VANDAL-PROOF BULLET AI LITE CAMERA (2/5 MP)**

AI / 0.002Lux Ultra Low-light / 60fps / IP66 / IP67 / IK10 / PoE (8 MP Optional)

**KEY FEATURE**

- AI Video Analytics
- Advanced Heat Map
- Face Detection Function
- Real-Time People Counting
- 4K Video Viewing Experience
- Leading-Edge H.265+ Compression




MODEL	AIS-NC2964-PD / AIS-MS2964(PD/PA/RPC)	AIS-NC5364-PD / AIS-MS5364(PD/PA/PC)
Image Sensor	1/2.8" Progressive Scan CMOS	1/2.8" Progressive Scan CMOS
WDR	Super WDR 140dB	Super WDR 120dB
Min. Illumination	Color: 0.002Lux@f.12 0.005Lux@F1.6	Color: 0.005Lux@f.12 0.008Lux@F1.6
Lens	2.8mm/4mm/6mm @F1.6	2.8mm/4mm/6mm @F1.6
Field of View	H111°/D128°/V61°(2.8mm)	H105°/ D131° / V78°
Mount	M12	M12
Shutter Time	1/100000s~1s	1/100000s~1s
IR Distance	Up to 30m	Up to 30m
Day & Night	Day/Night/Auto/Customize/Schedule	Day/Night/Auto/Customize/Schedule
S / N	>55dB	>55dB
Max. Image Resolution	60fps@(1920 x 1080)	30fps@(2592 x 1944)
Primary Stream	30fps@(1920x1080, 1280x960, 1280x720, 704x576)	
Secondary Stream	30fps@(704x576, 640x480, 640x360, 352x288, 320x240, 320x192, 320x180)	
Video Compression	H.265+ / H.265(HEVC)/H.264+/H.264/MJPEG	
Video Bit Rate	16Kbps~16Mbps(CBR/VBR Adjustable)	16Kbps~16Mbps(CBR/VBR Adjustable)
Face Detection	Detect and Capture Faces, Get Real-time Snapshots	
Ethernet	1*RJ45 10M/100M Ethernet Port	1*RJ45 10M/100M Ethernet Port
People Counting	Count the number of people entering or exiting, up to 4 detection areas for regional people counting	
Protocol	IPv4/IPv6, ARP, TCP, UDP, RTCP, RTP, RTSP, RTMP, HTTP, HTTPS, DNS, DDNS, DHCP, FTP, NTP, SMTP, SNMP, UPnP, Bonjour, SIP, PPPoE, VLAN, 802.1x, QoS, IGMP, ICMP, SSL	
Storage	NAS(Support NFS, SMB/CIFS); Support microSD/SDHC/SDXC Card Local Storage upto 256G (Optional)	
Advanced Function	Heat Map, Privacy Masking, BLC, HLC, 2D DNR, 3D DNR, Defog, AWB, EIS, IP Address Filtering	
Audio I/O	1/1 (Multi-interface Version)	1/1 (Multi-interface Version)
Event Trigger	Motion Detection, Network Disconnection, etc.	
Event Action	FTP Upload, SMTP Upload, SD Card Record, SIP Phone, HTTP Notification, etc.	
Video Analysis	Region Entrance, Region Exiting, Advanced Motion Detection	
System Compatibility	ONVIF Profile G & Q & S & T	ONVIF Profile G & Q & S & T
Working Temperature	-40°C ~ 60°C	-40°C ~ 60°C
Working Humidity	0~90%(Non-condensing)	0~90%(Non-condensing)
Power Supply	PoE (802.3af)	PoE (802.3af)
Power Consumption	2.5W MAX / 3.6W MAX (With IR on)	2.5W MAX / 3.6W MAX (With IR on)
Weather Proof	Up to IP67-rated for Weather-resistant Performance	
Housing	IP67/IK10	
Weight	450g (Cable Out Version) / 610g (Junction Box Version)	
Dimensions	97mmX74mmX180mm (Junction Box Version) / Ø64mmX160mm (Cable Out Version)	




## STRUCTURE DIAGRAMS


### CABLE OUT VERSION



### JUNCTION BOX VERSION



### SMART IR II TECHNOLOGY



### ACCESSORIES SUPPORT

AIS-A01 Pole Mount

Weight: 720g  
Dimensions: 170\*51.1\*152.6mm



AIS-A02 Internal Corner Bracket

Weight: 540g  
Dimensions: 170\*23.2\*205.3mm



AIS-A03 External Corner Bracket

Weight: 900g  
Dimensions: 170\*152.6\*76.3mm



**H.265+ VANDAL-PROOF MOTORIZED BULLET AI LITE CAMERA (2/5 MP)**

AI / 0.002Lux Ultra Low-light / 60fps / IP66 / IP67 / IK10 / PoE (8 MP Optional)

**KEY FEATURE**


- AI Video Analytics
- Advanced Heat Map
- Face Detection Function
- Advanced Motorized Lens
- Real-Time People Counting
- 4K Video Viewing Experience




MODEL	AIS-NC2964-MPD / AIS-MSC2964-R(T)F(I)PC	AIS-NC5364-MPD / AIS-MSC5364 F(I)PC
Image Sensor	1/2.8" Progressive Scan CMOS	1/2.8" Progressive Scan CMOS
WDR	Super WDR 140dB	Super WDR 120dB
Min. Illumination	Color: 0.002Lux@f.12 0.005Lux@F1.4	Color: 0.005Lux@f.12 0.008Lux@F1.4
Lens	Motorized 2.7~13.5mm/3.0~10.5mm/7~22mm@F1.4 P-Iris (Optional)	
Field of View	H111°~H34°/D130°~D39°/V60°~V19°	H99°~H31°/D124°~D38°/V72°~V23°
Mount	M12	M12
Shutter Time	1/100000s~1s	1/100000s~1s
IR Distance	Up to 50m	Up to 50m
Day & Night	Day/Night/Auto/Customize/Schedule	Day/Night/Auto/Customize/Schedule
S / N	>55dB	>55dB
Max. Image Resolution	60fps@(1920 x 1080)	30fps@(2592 x 1944)
Primary Stream	30fps@(1920x1080, 1280x960, 1280x720, 704x576)	
Secondary Stream	30fps@(704x576, 640x480, 640x360, 352x288, 320x240, 320x192, 320x180)	
Video Compression	H.265+ / H.265(HEVC)/H.264+/H.264/MJPEG	
Video Bit Rate	16Kbps~16Mbps(CBR/VBR Adjustable)	16Kbps~16Mbps(CBR/VBR Adjustable)
Face Detection	Detect and Capture Faces, Get Real-Time Snapshots	
Ethernet	1*RJ45 10M/100M Ethernet Port	1*RJ45 10M/100M Ethernet Port
People Counting	Count the number of people entering or exiting, up to 4 detection areas for regional people counting	
Protocol	IPv4/IPv6, ARP, TCP, UDP, RTCP, RTP, RTSP, RTMP, HTTP, HTTPS, DNS, DDNS, DHCP, FTP, NTP, SMTP, SNMP, UPnP, Bonjour, SIP, PPPoE, VLAN, 802.1x, QoS, IGMP, ICMP, SSL	
Storage	NAS(Support NFS, SMB/CIFS); Support microSD/SDHC/SDXC Card Local Storage upto 256G (Optional)	
Advanced Function	Heat Map, Privacy Masking, BLC, HLC, 2D DNR, 3D DNR, Defog, AWB, EIS, IP Address Filtering	
Audio I/O	1/1 (Multi-interface Version)	1/1 (Multi-interface Version)
Event Trigger	Motion Detection, Network Disconnection, etc.	
Event Action	FTP Upload, SMTP Upload, SD Card Record, SIP Phone, HTTP Notification, etc.	
Video Analysis	Region Entrance, Region Exiting, Advanced Motion Detection	
System Compatibility	ONVIF Profile G & Q & S & T	ONVIF Profile G & Q & S & T
Working Temperature	-40°C ~ 60°C	-40°C ~ 60°C
Working Humidity	0~90%(Non-condensing)	0~90%(Non-condensing)
Power Supply	PoE (802.3af) / DC 12V±10%	PoE (802.3af) / DC 12V±10%
Power Consumption	2.5W MAX / 3.6W MAX (With IR on)	2.5W MAX / 3.6W MAX (With IR on)
Weather Proof	Up to IP67-rated for Weather-resistant Performance	
Housing	IP67/IK10	IP67/IK10
Dimensions/Weight	∅76mm X 239.5mm / 825g	∅76mm X 239.5mm / 825g

## STRUCTURE DIAGRAMS


### CABLE OUT VERSION



### JUNCTION BOX VERSION



### SMART IR II TECHNOLOGY



### ACCESSORIES SUPPORT

AIS-A01 Pole Mount

Weight: 720g  
Dimensions: 170\*51.1\*152.6mm



AIS-A02 Internal Corner Bracket

Weight: 540g  
Dimensions: 170\*23.2\*205.3mm



AIS-A03 External Corner Bracket

Weight: 900g  
Dimensions: 170\*152.6\*76.3mm



**H.265 + WEATHER-PROOF DOME AI LITE CAMERA (2/5 MP)**

AI / 140dB WDR / 0.002Lux Ultra Low-light / 60fps / IP66 / IP67 / IK10 / PoE

**KEY FEATURE**


- AI Video Analytics
- Advanced Heat Map
- Face Detection Function
- Real-Time People Counting
- Advanced Built-in Microphone
- Reliable Anti-Vibration Performance




MODEL	AIS-NC2975-PD / AIS-MSC2975(PD/PA/PC)	AIS-NC5375-PD / AIS-MSC5375(PD/PA/PC)
Image Sensor	1/2.8" Progressive Scan CMOS	1/2.8" Progressive Scan CMOS
Min.Illumination	Color: 0.002Lux@F.12 0.005Lux@F1.6	Color: 0.005Lux@f.12 0.008Lux@F1.6
WDR	140dB Super WDR	Super WDR 120dB
Lens	2.8mm/4mm/6mm @F1.6	2.8mm/4mm/6mm @F1.6
Mount	M12	M12
Field of View	H111°/D128°/V61°(2.8mm)	H105°/D131°/V78°(2.8mm)
Shutter Time	1/100000s~1s	1/100000s~1s
IR Distance	Up to 25m	Up to 25m
Day & Night	Day/Night/Auto/Customize/Schedule	Day/Night/Auto/Customize/Schedule
S / N	>55dB	>55dB
Max. Image Resolution	60fps@(1920 x 1080)	30fps@(2592 x 1944)
Primary Stream	30fps@(1920x1080, 1280x960, 1280x720, 704x576)	
Face Detection	Detect and Capture Faces, Get Real-Time Snapshots	
Video Compression	H.265+/H.265(HEVC)/H.264+/H.264/MJPEG	H.265+/H.265(HEVC)/H.264+/H.264/MJPEG
Video Bit Rate	16Kbps~16Mbps(CBR/VBR Adjustable)	
Audio Compression	G.711/AAC/G.722/G.726	G.711/AAC/G.722/G.726
Ethernet	1*RJ45 10M/100M Ethernet Port	
People Counting	Count the number of people entering or exiting, up to 4 detection areas for regional people counting	
Protocol	IPv4/IPv6, ARP, TCP, UDP, RTCP, RTP, RTSP, RTMP, HTTP, HTTPS, DNS, DDNS, DHCP, FTP, NTP, SMTP, SNMP, UPnP, Bonjour,SIP, PPPoE, VLAN, 802.1x, QoS, IGMP, ICMP, SSL	
Storage	NAS(Support NFS, SMB/CIFS); Support microSD/SDHC/SDXC Card Local Storage upto 256G (Optional)	
Advanced Function	Heat Map, Privacy Masking, BLC, HLC, 2D DNR, 3D DNR, Defog, AWB, EIS, IP Address Filtering	
Audio I/O	1/1 (Multi-interface Version)	1/1 (Multi-interface Version)
Event Trigger	Motion Detection, Network Disconnection, etc.	
Event Action	FTP Upload, SMTP Upload, SD Card Record, SIP Phone, HTTP Notification, etc.	
Video Analysis	Region Entrance, Region Exiting, Advanced Motion Detection	
System Compatibility	ONVIF Profile G & Q & S & T	ONVIF Profile G & Q & S & T
Working Temperature	-40°C ~ 60°C	-40°C ~ 60°C
Working Humidity	0~90%(Non-condensing)	
Power Supply	PoE (802.3af)	
Power Consumption	2.5W MAX	
Housing	IP67/IK10	IP67/IK10
Audio	Built-in Microphone	
Weight	410g (Cable Out Version)	600g (Junction Box Version)
Dimensions	Φ106mmX76.5mm (Cable Out Version) / Φ108mmX96.5mm (Junction Box Version)	

## STRUCTURE DIAGRAMS

### CABLE OUT VERSION



### JUNCTION BOX VERSION



## ACCESSORIES SUPPORT

AIS-A01 Pole Mount

Weight: 720g  
Dimensions: 170\*51.5\*152.6mm



AIS-A02 Internal Corner Bracket

Weight: 540g  
Dimensions: 170\*23.2\*205.3mm



AIS-A03 External Corner Bracket

Weight: 900g  
Dimensions: 170\*152.6\*76.3mm



AIS-A71 Wall Mount

Weight: 530g  
Dimensions: 162-124-78mm



AIS-A73 Adapter Plate

Weight: 28g  
Dimensions: 115\*122.5\*10mm



**H.265+ WEATHER-PROOF AF MOTORIZED DOME AI LITE CAMERA (2/5 MP)**

ONVIF | G | Q | S | T

AI / 140dB WDR / 0.002Lux Ultra Low-light / 60fps / IP66 / IP67 / IK10 / PoE

**KEY FEATURE**


- AI Video Analytics
- Advanced Heat Map
- Face Detection Function
- Real-Time People Counting
- Advanced Built-in Microphone
- Reliable Anti-Vibration Performance




MODEL	AIS-NC2975-AFPD / AIS-MSC2975(PD/PA/REPC)	AIS-NC5375-AFPD / AIS-MSC5375(PD/PA/EPC)
Image Sensor	1/2.8" Progressive Scan CMOS	1/2.8" Progressive Scan CMOS
Min.Illumination	Color: 0.002Lux@F.12 0.005Lux@F1.8	Color: 0.005Lux@f.12 0.008Lux@F1.8
WDR	140dB Super WDR	Super WDR 120dB
Lens	2.8~8.4mm, 3X Optical Zoom	2.8~8.4mm, 3X Optical Zoom
Mount	M12	M12
Field of View	H111°~ H48°/D130°~D55°/V60°~V27°	H101°~H42°/D129°~D53°/V74°~V31°
Shutter Time	1/100000s~1s	1/100000s~1s
IR Distance	Up to 35m	Up to 35m
Day & Night	Day/Night/Auto/Customize/Schedule	Day/Night/Auto/Customize/Schedule
S / N	>55dB	>55dB
Max. Image Resolution	60fps@(1920 x 1080)	30fps@(2592 x 1944)
Primary Stream	30fps@(1920x1080, 1280x960, 1280x720, 704x576)	
Face Detection	Detect and Capture Faces, Get Real-Time Snapshots	
Video Compression	H.265+/H.265(HEVC)/H.264+/H.264/MJPEG	H.265+/H.265(HEVC)/H.264+/H.264/MJPEG
Video Bit Rate	16Kbps~16Mbps(CBR/VBR Adjustable)	16Kbps~16Mbps(CBR/VBR Adjustable)
Audio Compression	G.711/AAC/G.722/G.726	G.711/AAC/G.722/G.726
Ethernet	1*RJ45 10M/100M Ethernet Port	1*RJ45 10M/100M Ethernet Port
People Counting	Count the number of people entering or exiting, up to 4 detection areas for regional people counting	
Protocol	IPv4/IPv6, ARP, TCP, UDP, RTCP, RTP, RTSP, RTMP, HTTP, HTTPS, DNS, DDNS, DHCP, FTP, NTP, SMTP, SNMP, UPnP, Bonjour,SIP, PPPoE, VLAN, 802.1x, QoS, IGMP, ICMP, SSL	
Storage	NAS(Support NFS, SMB/CIFS); Support microSD/SDHC/SDXC Card Local Storage upto 256G (Optional)	
Advanced Function	Heat Map, Privacy Masking, BLC, HLC, 2D DNR, 3D DNR, Defog, AWB, EIS, IP Address Filtering	
Audio I/O	1/1 (Multi-interface Version)	
Event Trigger	Motion Detection, Network Disconnection, External Input, Audio Alarm.	
Event Action	FTP Upload, SMTP Upload, SD Card Record, External Output, SIP Phone, HTTP Notification.	
Video Analysis	Region Entrance, Region Exiting, Advanced Motion Detection	
System Compatibility	ONVIF Profile G & Q & S & T	ONVIF Profile G & Q & S & T
Working Temperature	-40°C ~ 60°C	-40°C ~ 60°C
Working Humidity	0~90%(Non-condensing)	0~90%(Non-condensing)
Power Supply	PoE (802.3af) / DC 12V±10%	PoE (802.3af) / DC 12V±10%
Power Consumption	2.5W MAX	2.5W MAX
Housing	IP67/IK10	IP67/IK10
Audio	Built-in Microphone	Built-in Microphone
Weight	410g (Cable Out Version)	600g (Junction Box Version)
Dimensions/Weight	108mmX96.5mm/620g	Φ108mmX96.5mm/620g

## STRUCTURE DIAGRAMS

### CABLE OUT VERSION



### JUNCTION BOX VERSION



## ACCESSORIES SUPPORT

**AIS-A01 Pole Mount**

Weight: 720g  
Dimensions: 170\*51.5\*152.6mm



**AIS-A02 Internal Corner Bracket**

Weight: 540g  
Dimensions: 170\*23.2\*205.3mm



**AIS-A03 External Corner Bracket**

Weight: 900g  
Dimensions: 170\*152.6\*76.3mm



**AIS-A71 Wall Mount**

Weight: 530g  
Dimensions: 162-124-78mm



**AIS-A73 Adapter Plate**

Weight: 28g  
Dimensions: 115\*122.5\*10mm



**H.265+ VANDAL-PROOF DOME AI LITE CAMERA (2/5 MP)**

AI / 0.002Lux Ultra Low-light / 60fps / EN50155 / IP66 / IP67 / IK10 / PoE (8 MP Optional)

ONVIF | G Q S T

**KEY FEATURE**



- AI Video Analytics
- Advanced Heat Map
- Face Detection Function
- Real-Time People Counting
- 4K Video Viewing Experience
- Reliable Anti-Vibration Performance



MODEL	AIS-NC2973-PD / AIS-MSC2973(PD/PA/PC)	AIS-NC5373-PD / AIS-MSC5373(PD/PA/PC)
Image Sensor	1/2.8" Progressive Scan CMOS	1/2.8" Progressive Scan CMOS
Min.Illumination	Color: 0.002Lux@f.12 0.005Lux@F1.4	Color: 0.005Lux@f.12 0.008Lux@F1.4
WDR	140dB Super WDR	Super WDR 120dB
Lens	2.8mm/4mm/6mm @F1.6	2.8mm/4mm/6mm @F1.6
Mount	M12	M12
Field of View	H111°/D128°/V61°(2.8mm) H91°/D106°/V50°(4mm) H55°/D63°/V32°(6mm)	
Shutter Time	1/100000s~1s	1/100000s~1s
IR Distance	Up to 30m	Up to 30m
Day & Night	Day/Night/Auto/Customize/Schedule	Day/Night/Auto/Customize/Schedule
S / N	>55dB	>55dB
Max. Image Resolution	60fps@(1920 x 1080)	30fps@(2592 x 1944)
Primary Stream	30fps@(1920x1080, 1280x960, 1280x720, 704x576)	
Secondary Stream	30fps@(704x576, 640x480, 640x360, 352x288, 320x240, 320x192, 320x180)	
Video Compression	H.265+/H.265(HEVC)/H.264+/H.264/MJPEG	H.265+/H.265(HEVC)/H.264+/H.264/MJPEG
Video Bit Rate	16Kbps~16Mbps(CBR/VBR Adjustable)	16Kbps~16Mbps(CBR/VBR Adjustable)
Face Detection	Detect and Capture Faces, Get Real-Time Snapshots	
Ethernet	1*RJ45 10M/100M Ethernet Port	1*RJ45 10M/100M Ethernet Port
People Counting	Count the number of people entering or exiting, up to 4 detection areas for regional people counting	
Protocol	IPv4/IPv6, ARP, TCP, UDP, RTCP, RTP, RTSP, RTMP, HTTP, HTTPS, DNS, DDNS, DHCP, FTP, NTP, SMTP, SNMP, UPnP, Bonjour,SIP, PPPoE, VLAN, 802.1x, QoS, IGMP, ICMP, SSL	
Storage	NAS(Support NFS, SMB/CIFS); Support microSD/SDHC/SDXC Card Local Storage upto 256G (Optional)	
Advanced Function	Heat Map, Privacy Masking, BLC, HLC, 2D DNR, 3D DNR, Defog, AWB, EIS, IP Address Filtering	
Audio I/O	1/1 (Multi-interface Version)	1/1 (Multi-interface Version)
Event Trigger	Motion Detection, Network Disconnection, etc.	
Event Action	FTP Upload, SMTP Upload, SD Card Record, SIP Phone, HTTP Notification, etc.	
Video Analysis	Region Entrance, Region Exiting, Advanced Motion Detection	
System Compatibility	ONVIF Profile G & Q & S & T	ONVIF Profile G & Q & S & T
Working Temperature	-40°C ~ 60°C	-40°C ~ 60°C
Working Humidity	0~90%(Non-condensing)	0~90%(Non-condensing)
Power Supply	PoE (802.3af)	PoE (802.3af)
Power Consumption	3.5W MAX (With IR on)	3.5W MAX (With IR on)
Weather Proof	Up to IP67-rated for Weather-resistant Performance	
Housing	IP67/IK10	IP67/IK10
Weight	500g	500g
Dimensions	118.5mmX110.8mmX65mm	118.5mmX110.8mmX65mm



## STRUCTURE DIAGRAMS



## ACCESSORIES SUPPORT

**AIS-A01 Pole Mount**

Weight: 720g  
Dimensions: 170\*51.5\*152.6mm



**AIS-A02 Internal Corner Bracket**

Weight: 540g  
Dimensions: 170\*23.2\*205.3mm



**AIS-A03 External Corner Bracket**

Weight: 900g  
Dimensions: 170\*152.6\*76.3mm



**AIS-A71 Wall Mount**

Weight: 530g  
Dimensions: 162-124-78mm



**AIS-A73 Adapter Plate**

Weight: 28g  
Dimensions: 115\*122.5\*10mm



**AIS-A74 Junction Box**

Weight: 60g  
Dimensions: 121.5\*116.5\*37.2mm





San Carlos Business and Technology Park,  
Industrial Road, CA 94070 - USA  
Email us at [enquiry@alcosolutions.net](mailto:enquiry@alcosolutions.net)  
Web: [www.alcosolutions.net](http://www.alcosolutions.net)