

H.265+ PRO BULLET CAMERA (2/5/8 MP)

H.265+ / 3 Axis Mechanical Design / IP67 / IK10 / SIP

ONVIF | G | Q | S | T



KEY FEATURE

- 0.002Lux Starlight
- 140dB Super WDR
- Smart IR II With 50m IR Distance
- 120 Wide Angle Viewing Experience
- 60fps High Frame Rate
- Embedded VCA as Standard
- Unique Sunshield Design



Model	AIS-NC2963-RPC	AIS-NC5363-PC	AIS-NC8163-PC
Megapixel	2MP	5MP	4K
Image Sensor	1/2.8" Progressive Scan CMOS	1/2.8" Progressive Scan CMOS	1/2.8" Progressive Scan CMOS
Lens	4mm / 2.8 mm / 6mm @ F1.6	4mm / 2.8 mm / 6mm @ F1.6	4mm / 2.8 mm / 6mm @ F1.6
Field of View	H91 / D106 / V50 (4mm)	H86 / D708 / V63 (4mm)	H91 / D106 / V50 (4mm)
WDR	Super WDR 140dB	Super WDR 120dB	Super WDR 120dB
Max. Frame Rate	60fps@(1920 x 1080)	30fps@(2592 x 1944)	30fps@(3840 x 2160)
Min. Illumination	Color: 0.002Lux @ F1.2 B/W: 0Lux with IR on	Color: 0.005Lux @ F1.2 B/W: 0Lux with IR on	Color: 0.01Lux @ F1.2 B/W: 0Lux with IR on
Video Compression	H.265+ / H.265(HEVC)/H.264/H.264/MJPEG	H.265+ / H.265(HEVC)/H.264/H.264/MJPEG	H.265+ / H.265(HEVC)/H.264/H.264/MJPEG
Protocol	IPV4/IPV6, ARP, TCP, UDP, RTCP, RTP, RTSP, RTMP, HTTP, HTTPS, DNS, DDNS, DHCP, FTP, NTP, SMTP, SNMP, UPnP, Bonjour, SIP, PPPoE, VLAN, 802.1x, QoS, IGMP, ICMP, SSL		
Dimensions/Weight	76mm X 214.5mm / 750g	76mm X 214.5mm / 750g	76mm X 214.5mm / 750g