

## H.265+ VANDAL-PROOF PRO DOME CAMERA (2/5/8 MP)

H.265+ / IP67 / 3 Axis Mechanical Design / IK10 / PoE



### KEY FEATURE

- 0.002Lux Starlight
- 140dB Super WDR
- Smart IR II With 30m IR Distance
- 120 Wide Angle Viewing Experience
- 60fps High Frame Rate
- Embedded VCA as Standard
- UL Certificated



| Model             | AIS-NC2973-RPC   | AIS-NC5373-PC                                  | AIS-NC8173-PC                                 |
|-------------------|--|--|---|
| Megapixel         | 2MP  | 5MP  | 4K  |
| Image Sensor      | 1/2.8" Progressive Scan CMOS   | 1/2.8" Progressive Scan CMOS                   | 1/2.8" Progressive Scan CMOS                  |
| Lens              | 2.8mm @ F2.0 / 4mm @ F1.6  | 2.8mm @ F2.0 / 4mm @ F1.6                      | 2.8mm @ F2.0 / 4mm @ F1.6                     |
| Field of View     | H123 / D142 / V68 (2.8mm)  | H111 / D141 / V82 (2.8mm)                      | H124 / D140 / V69 (2.8mm)                     |
| WDR               | 140dB Super WDR  | 120dB Super WDR                                | 120dB Super WDR                               |
| Max. Frame Rate   | 60fps@(1920 x 1080)  | 30fps@(2592 x 1944)                            | 30fps@(3840 x 2160)                           |
| Min. Illumination | Color: 0.002Lux @ F1.2<br>B/W: 0Lux with IR on   | Color: 0.005Lux @ F1.2<br>B/W: 0Lux with IR on | Color: 0.01Lux @ F1.2<br>B/W: 0Lux with IR on |
| Video Compression | H.265+ / H.265(HEVC)/H.264/H.264/MJPEG   | H.265 / H.265(HEVC)/H.264/H.264/MJPEG          | H.265 / H.265(HEVC)/H.264/H.264/MJPEG         |
| Protocol          | IPv4/IPv6, ARP, TCP, UDP, RTP, RTSP, RTMP, HTTP, HTTPS, DNS, DDNS, DHCP, FTP, NTP, SMTP, SNMP, UPnP, Bonjour, SIP, PPPoE, VLAN, 802.1x, QoS, IGMP, ICMP, SSL |  |   |
| Dimensions/Weight | 118.5mm X 110.8mm X 65mm / 500g  | 118.5mm X 110.8mm X 65mm / 500g                | 118.5mm X 110.8mm X 65mm / 500g               |