

H.265+ WEATHER-PROOF PRO DOME CAMERA (2/5 MP)

H.265+ / 3 Axis Mechanical Design / IP66 / IK10 / Clamshell Design / PoE

Onvif | G Q S T



KEY FEATURE

- 0.002Lux Starlight
- 140dB Super WDR
- Smart IR II With 25m IR Distance
- 120 Wide Angle Viewing Experience
- Integrated Junction Box
- Embedded VCA as Standard
- Built-in Microphone



Model	AIS-NC2975-RPC	AIS-NC5375-PC
Megapixel	2MP	5MP
Image Sensor	1/2.8" Progressive Scan CMOS	1/2.8" Progressive Scan CMOS
Lens	2.8mm @ F2.0 / 4mm @ F1.6	2.8mm @ F2.0 / 4mm @ F1.6
Field of View	H123 / D142 / V68 (2.8mm)	H113 / D144 / V84 (2.8mm)
WDR	Super WDR up to 140dB	Super WDR up to 120dB
Max. Frame Rate	60fps@(1920 x 1080)	30fps@(2048 x 1536)
Min. Illumination	Color: 0.002Lux @ F1.2 B/W: 0Lux with IR on	Color: 0.005Lux @ F1.2 B/W: 0Lux with IR on
Video Compression	H.265 / H.265(HEVC)/H.264/H.264/MJPEG	H.265 / H.265(HEVC)/H.264/H.264/MJPEG
Protocol	IPv4/IPv6, ARP, TCP, UDP, RTP, RTSP, RTMP, HTTP, HTTPS, DNS, DDNS, DHCP, FTP, NTP, SMTP, SNMP, UPnP, Bonjour, SIP, PPPoE, VLAN, 802.1x, QoS, IGMP, ICMP, SSL	
Dimensions/Weight	108mm X 96.5mm / 600g (Junction Box Version)	106mm X 76.5mm / 410g (Cable Out Version)