

H.265+ PRO DOME CAMERA (2/5/8 MP)

H.265+ / 3 Axis Mechanical Design / PoE / IP67



KEY FEATURE

- 0.002Lux Starlight
- 140dB Super WDR
- Smart IR II With 20m IR Distance
- 120 Wide Angle Viewing Experience
- 60fps High Frame Rate
- Embedded VCA as Standard
- Built-in Microphone



Model	AIS-NC2983-RPC	AIS-NC5383-PC	AIS-NC8183-PC
Megapixel	2MP	5MP	4K
Image Sensor	1/2.8" Progressive Scan CMOS	1/2.8" Progressive Scan CMOS	1/2.8" Progressive Scan CMOS
Lens	2.8mm @ F2.0 / 4mm @ F1.6 / 6mm @ F1.6	2.8mm @ F2.0 / 4mm @ F1.6 / 6mm @ F1.6	2.8mm @ F2.0 / 4mm @ F1.6 / 6mm @ F1.6
Field of View	H124 / D144 / V68 (2.8mm)	H113 / D143 / V83 (2.8mm)	H124 / D140 / V69 (2.8mm)
WDR	Super WDR up to 140dB	Super WDR up to 120dB	Super WDR up to 120dB
Max. Frame Rate	60fps@(1920 x 1080)	30fps@(2592 x 1944)	30fps@(3840 x 2160)
Min. Illumination	Color: 0.002Lux @ F1.2 B/W: 0Lux with IR on	Color: 0.005Lux @ F1.2 B/W: 0Lux with IR on	Color: 0.01Lux @ F1.2 B/W: 0Lux with IR on
Video Compression	H.265 / H.265(HEVC)/H.264/H.264/MJPEG	H.265 / H.265(HEVC)/H.264/H.264/MJPEG	H.265 / H.265(HEVC)/H.264/H.264/MJPEG
Protocol	IPv4/IPv6, ARP, TCP, UDP, RTP, RTSP, RTMP, HTTP, HTTPS, DNS, DDNS, DHCP, FTP, NTP, SMTP, SNMP, UPnP, Bonjour, SIP, PPPoE, VLAN, 802.1x, QoS, IGMP, ICMP, SSL		
Dimensions/Weight	97.8mm X 57.9mm / 200g		

BLACK

WHITE