

H.265+ VANDAL-PROOF MOTORIZED BULLET CAMERA (2/5/8 MP)

H.265+ / 3 Axis Mechanical Design / IP67 / IK10 / PoE & DC / SIP



KEY FEATURE

- 0.001Lux Starlight
- 3 in 1 Super WDR - 140dB
- 120fps High Frame Rate
- Smart IR II with 140m IR Distace
- Embedded VCA as Standard
- Intrgrated Sunshield Design
- Powerful Auto Back Focus



Model	AIS-NC2952-(PD/PA/TPC)	AIS-NC5352-(PD/PA/PC)	AIS-NC8152-(PD/PA/PC)
Megapixel	2MP	5MP	4K
Image Sensor	1/2" Progressive Scan CMOS	1/2.8" Progressive Scan CMOS	1/2.8" Progressive Scan CMOS
Mount & Iris	C/CS & P-Iris / DC-Iris	C/CS & P-Iris / DC-Iris	C/CS & P-Iris / DC-Iris
WDR	140dB Super WDR	120dB Super WDR	120dB Super WDR
Max. Frame Rate	60fps@(1920 x 1080)	30fps@(2592 x 1944)	30fps@(3840 x 2160)
Min. Illumination	Color: 0.001Lux @ F1.2 B/W: 0Lux with IR on	Color: 0.002Lux @ F1.2 B/W: 0Lux with IR on	Color: 0.01Lux @ F1.2 B/W: 0Lux with IR on
Video Compression	H.265+ / H.265(HEVC)/H.264/H.264/MJPEG	H.265+ / H.265(HEVC)/H.264/H.264/MJPEG	H.265+ / H.265(HEVC)/H.264/H.264/MJPEG
Protocol	IPv4/IPv6,ARP,TCP,UDP,RTCP,RTP,RTSP,RTMP,HTTP,HTTPS,DNS,DDNS,DHCP,FTP,NTP,SMTP,SNMP,UPnP,Bonjour,SIP,PPPoE,VLAN,802.1x,QoS,IGMP,ICMP,SSL		
Dimensions/Weight	115mm X 62mm X 50mm / 407g	115mm X 62mm X 50mm / 407g	115mm X 62mm X 50mm / 407g