

H.265+ MOTORIZED PRO PLUS BULLET CAMERA (2/5/8 MP)

H.265+ / Motorized Zoom Lens / 3 Axis Mechanical Design / IP67 / IK10 / SIP

KEY FEATURE

- 1/1.8 STARVIS Starlight Sensor
- 0.001Lux Starlight
- 3 in 1 Super WDR - 140dB
- 120fps High Frame Rate
- Smart IR II with 50m IR Distace
- Embedded VCA as Standard
- Intrgrated Sunshield Design



Model	AIS-NC2962-MPD / R(T)F(I)PC	AIS-NC5362-MPD / F(I)PC	AIS-NC8162-MPD / F(I)PC
Megapixel	2MP	5MP	4K
Image Sensor	1/2" Progressive Scan CMOS	1/2.8" Progressive Scan CMOS	1/1.8" Progressive Scan CMOS
Lens	Motorized 3.6-10mm @ f1.4 P-Iris	Motorized 3.0-10.5mm @ f1.4 P-Iris	Motorized 3.6-10mm @ f1.4 P-Iris
Field of View	H96-H42 / D111-D48 / V55-V23	H93-H32 / D107-D38 / V52-V18	H110-H46 / D126-D54 / V61-V25
WDR	140dB Super WDR	140dB Super WDR	120dB Super WDR
Max. Frame Rate	60fps@(1920 x 1080)	30fps@(2592 x 1944)	15fps@(3840 x 2160)
Min. Illumination	Color: 0.001Lux @ F1.2 B/W: 0Lux with IR on	Color: 0.002Lux @ F1.2 B/W: 0Lux with IR on	Color: 0.01Lux @ F1.2 B/W: 0Lux with IR on
Video Compression	H.265+ / H.265(HEVC)/H.264/H.264/MJPEG	H.265+ / H.265(HEVC)/H.264/H.264/MJPEG	H.265+ / H.265(HEVC)/H.264/H.264/MJPEG
Protocol	IPv4/IPv6, ARP, TCP, UDP, RTCP, RTP, RTSP, RTMP, HTTP, HTTPS, DNS, DDNS, DHCP, FTP, NTP, SMTP, SNMP, UPnP, Bonjour, SIP, PPPoE, VLAN, 802.1x, QoS, IGMP, ICMP, SSL		
Dimensions/Weight	134mm X 126mm X 285 / 1080g	134mm X 126mm X 285 / 1080g	134mm X 126mm X 285 / 1080g