

H.265+ MOTORIZED PRO PLUS DOME CAMERA (2/5/8 MP)

H.265+ / Motorized Zoom Lens / 3 Axis Mechanical Design / IP66 / IK10 / SIP

KEY FEATURE

- 0.002Lux Starlight
- 140dB Super WDR
- Smart IR II With 30m IR Distance
- 120 Wide Angle Viewing Experience
- 60fps High Frame Rate
- Embedded VCA as Standard
- UL Certificated



Model	AIS-NC2972-MPD / R(T)F(I)PC	AIS-NC5372-MPD / F(I)PC	AIS-NC8172-MPD / F(I)PC
Megapixel	2MP	5MP	4K
Image Sensor	1/2." Progressive Scan CMOS	1/2.8" Progressive Scan CMOS	1/2.8" Progressive Scan CMOS
Lens	Motorized 3.6-10mm @ f1.4 P-Iris	Motorized 3.0-10.5mm @ f1.4 P-Iris	Motorized 2.7-13.5mm @ f1.4 P-Iris
Field of View	H123 / D142 / V68 (2.8mm)	H111 / D141 / V82 (2.8mm)	H124 / D140 / V69 (2.8mm)
WDR	140dB Super WDR	120dB Super WDR	120dB Super WDR
Max. Frame Rate	60fps@(1920 x 1080)	30fps@(2592 x 1944)	30fps@(3840 x 2160)
Min. Illumination	Color: 0.002Lux @ F1.2 B/W: 0Lux with IR on	Color: 0.005Lux @ F1.2 B/W: 0Lux with IR on	Color: 0.01Lux @ F1.2 B/W: 0Lux with IR on
Video Compression	H.265+ / H.265(HEVC)/H.264/H.264/MJPEG	H.265+ / H.265(HEVC)/H.264/H.264/MJPEG	H.265+ / H.265(HEVC)/H.264/H.264/MJPEG
Protocol	IPv4/IPv6,ARP,TCP,UDP,RTCP,RTP,RTSP,RTMP,HTTP,HTTPS,DNS,DDNS,DHCP,FTP,NTP,SMTP,SNMP,UPnP,Bonjour,SIP,PPPoE,VLAN,802.1x,QoS,IGMP,ICMP,SSL		
Dimensions/Weight	143mm X 108.4mm / 1100g	143mm X 108.4mm / 1100g	143mm X 108.4mm / 1100g