

H.265+ 12X PTZ BULLET CAMERA (2/5 MP)

H.265+ / PTZ Privacy Mask / 3D Positioning / IP66 / SIP



KEY FEATURE

- 360 Endless Pan & 75 Tilt
- 12X Optical Zoom
- Smart IR II With 140m IR Distance
- PTZ Auto Tracking
- Integrated White LED
- Embedded VCA as Standard
- 0.002Lux Starlight



Wall Mount



Pedestal Mount



Model	AIS-NC2961-X12PB / R(T)PC	AIS-NC5361-X12PB / PC
Megapixel	2MP	5MP
Image Sensor	1/2.8" Progressive Scan CMOS	1/2.8" Progressive Scan CMOS
Lens	5.3 - 66mm @ F1.6 - F2.8, 12X Optical Zoom	5.3 - 66mm @ F1.6 - F2.8, 12X Optical Zoom
Field of View	H61- H5 / D69 - D5 / V36 - V2	H57 - H4 / D69 - D5 / V44 - V1
WDR	Super WDR up to 140dB	Super WDR up to 120dB
Tilt Range	360 Endless: Pan Manual Speed: 0.2 - 60/s	360 Endless: Pan Manual Speed: 0.2 - 60/s
Pan Speed	-45 -30: Tilt Manual Speed 0.2 - 30/s	-45 -30: Tilt Manual Speed 0.2 - 30/s
Min. Illumination	Color: 0.002Lux @ F1.2 B/W: 0Lux with IR on	Color: 0.005Lux @ F1.2 B/W: 0Lux with IR on
Video Compression	H.265+ / H.265(HEVC)/H.264/H.264/MJPEG	H.265+ / H.265(HEVC)/H.264/H.264/MJPEG
Protocol	IPv4/IPv6, ARP, TCP, UDP, RTCP, RTP, RTSP, RTMP, HTTP, HTTPS, DNS, DDNS, DHCP, FTP, NTP, SMTP, SNMP, UPnP, Bonjour, SIP, PPPoE, VLAN, 802.1x, QoS, IGMP, ICMP, SSL	
Dimensions/Weight	160mm X 273.5mm X 210mm / 2Kg (Wall Mount)	218mm X 120mm X 1.8Kg (Pedestal Mount)