

23X / 30X / H.265+ SPEED DOME CAMERA (2/5 MP)

H.265+ / PTZ Privacy Mask / 3D Positioning / IP66 / IK10 / SIP / PoE



KEY FEATURE

- 360 Endless Pan & 90 Auto-Filp Tilt
- 23 X 30 X Optical Zoom
- Smart IR II Withup to 200m IR Distance
- 120 Wide Angle Viewing Experience
- 140fps Super WDR
- Embedded VCA as Standard
- 0.002Lux Starlight



Model	AIS-NC2941-X23PC / R(T)PC	AIS-NC5341-X23PC
Megapixel	2MP	5MP
Image Sensor	1/2.8" Progressive Scan CMOS	1/2.8" Progressive Scan CMOS
Lens	5.0 - 117mm @ F1.5 - F3.5, 23X Optical Zoom	5.0 - 141mm @ F1.5 - F4.0, 23X Optical Zoom
Field of View	H61- H5 / D69 - D5 / V36 - V2	H57 - H4 / D71 - D3 / V44 - V2
WDR	Super WDR up to 140dB	Super WDR up to 120dB
Tilt Range	360 Endless: Pan Manual Speed: 0.2 - 60/s	360 Endless: Pan Manual Speed: 0.2 - 60/s
Pan Speed	-45 -30: Tilt Manual Speed 0.2 - 30/s	-45 -30: Tilt Manual Speed 0.2 - 30/s
Min. Illumination	Color: 0.002Lux @ F1.2 B/W: 0Lux with IR on	Color: 0.005Lux @ F1.2 B/W: 0Lux with IR on
Video Compression	H.265+ / H.265(HEVC)/H.264/H.264/MJPEG	H.265+ / H.265(HEVC)/H.264/H.264/MJPEG
Protocol	IPv4/IPv6, ARP, TCP, UDP, RTCP, RTP, RTSP, RTMP, HTTP, HTTPS, DNS, DDNS, DHCP, FTP, NTP, SMTP, SNMP, UPnP, Bonjour, SIP, PPPoE, VLAN, 802.1x, QoS, IGMP, ICMP, SSL	
Dimensions/Weight	205mm X 308mm / 4Kg	205mm X 308mm / 4Kg