

36X / 42X / H.265+ SPEED DOME CAMERA (2/5/8 MP)

H.265+ / PTZ Privacy Mask / 3D Positioning / IP66 / IK10 / SIP / PoE



KEY FEATURE

- 360 Endless Pan & 90 Auto-Flip Tilt
- 36 X 42 X Optical Zoom
- Smart IR II With up to 300m IR Distance
- 1/1.8 Starvis Starlight Sensor
- 140fps Super WDR
- Embedded VCA as Standard
- Pan Speed 400/s, Tilt Speed 350/s



Model	AIS-NC2941-X42PC / R(T)PC	AIS-NC5341-X42PC	AIS-NC8241-X42PC
Megapixel	2MP	5MP	4K
Image Sensor	1/2" Progressive Scan CMOS	1/2.8" Progressive Scan CMOS	1/1.8" Progressive Scan CMOS
Lens	5.0 - 205.2mm 41X Optical Zoom	5.7 - 205.2mm 41X Optical Zoom	7.0 - 300mm 41X Optical Zoom
Field of View	H93-H3 / D69-D3 / V38-V1	H45-H2 / D50-D2 / V27-V1	H66-H3 / D72-D3 / V41-V1
WDR	140dB Super WDR	140dB Super WDR	120dB Super WDR
Max. Frame Rate	90fps@(1920 x 1080) 60fps@(1920 x 1080)	60fps@(2592 x 1944) 30fps@(2592 x 1944)	30fps@(3840 x 2160)
Min. Illumination	Color: 0.001Lux @ F1.2 B/W: 0Lux with IR on	Color: 0.002Lux @ F1.2 B/W: 0Lux with IR on	Color: 0.01Lux @ F1.2 B/W: 0Lux with IR on
Video Compression	H.265+ / H.265(HEVC)/H.264/H.264/MJPEG	H.265+ / H.265(HEVC)/H.264/H.264/MJPEG	H.265+ / H.265(HEVC)/H.264/H.264/MJPEG
Protocol	IPV4/IPV6, ARP, TCP, UDP, RTCP, RTP, RTSP, RTMP, HTTP, HTTPS, DNS, DDNS, DHCP, FTP, NTP, SMTP, SNMP, UPnP, Bonjour, SIP, PPPoE, VLAN, 802.1x, QoS, IGMP, ICMP, SSL		
Dimensions/Weight	205mm X 308mm / 4kg	205mm X 308mm / 4kg	205mm X 308mm / 4kg